



Bearing No. 29480E

|                               |                  |
|-------------------------------|------------------|
| Size                          | 400x710x185 mm   |
| Bore Diameter                 | 400 mm           |
| Outer Diameter                | 710 mm           |
| Width                         | 185 mm           |
| d                             | 400 mm           |
| D                             | 710 mm           |
| T                             | 185 mm           |
| d1                            | 680 mm           |
| r min.                        | 7.5 mm           |
| A                             | 236 mm           |
| B1                            | 67 mm            |
| B2                            | 178 mm           |
| C                             | 89 mm            |
| D1                            | 534 mm           |
| da min.                       | 540 mm           |
| Da max.                       | 610 mm           |
| ra max.                       | 6 mm             |
| Weight                        | 314 Kg           |
| Basic dynamic load rating (C) | 5850 kN          |
| Basic static load rating (C0) | 25000 kN         |
| Bore Type                     | Cylindrical Bore |
| Enclosure                     | Open             |
| Configuration                 | Single Row       |
| Bore Size                     | 400 mm           |
| Outside Diameter              | 710 mm           |
| Fillet Radius/Chamfer         | 7.5 mm           |
| Width                         | 185 mm           |
| Dynamic Load Rating           | 5,850,000 N      |
| Static Load Rating            | 25,000,000 N     |

|                      |         |
|----------------------|---------|
| Limiting Speed - Oil | 360 rpm |
| B                    | 67 mm   |
| da (min)             | 540 mm  |
| Da (max)             | 610 mm  |
| ra (max)             | 6 mm    |