



Bearing No. NU 226 ECML

Size	230x130x40 mm
Bore Diameter	230 mm
Outer Diameter	130 mm
Width	40 mm
d	130 mm
D	230 mm
B	40 mm
D ₁	201.2 mm
F	153.5 mm
r _{1,2} - min.	3 mm
r _{3,4} - min.	3 mm
s	2.1 mm
d _a - min.	144 mm
d _a - max.	150 mm
d _b - min.	157 mm
D _a - max.	215.4 mm
r _a - max.	2.5 mm
r _b - max.	2.5 mm
Basic dynamic load rating - C	415 kN
Basic static load rating - C ₀	455 kN
Fatigue load limit - P _u	51 kN
Reference speed	3200 r/min
Limiting speed	5300 r/min
Calculation factor - k _r	0.23
Category	Cylindrical Roller Bearings
BDI Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	7.229
EAN	7316577053954
Product Group - BDI	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	130MM Bore; Straight Bore Profile; 230MM Outside Diameter; 40MM Width; Brass Cage Matetrial; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Internal Clearance; Retainer
Category - BDI	Cylindrical Roller Bearing
UNSPSC	31171547

Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 226 ECML
Weight / LBS	15.922
Outside Diameter	9.055 Inch 230 Millimeter
Bore	5.118 Inch 130 Millimeter
Width	1.575 Inch 40 Millimeter
D_1 ?	201.2 mm
$r_{1,2}$ min.	3 mm
$r_{3,4}$ min.	3 mm
s max.	2.1 mm
d_a min.	144 mm
d_a max.	150 mm
d_b min.	157 mm
D_a max.	215.4 mm
r_a max.	2.5 mm
r_b max.	2.5 mm
Basic dynamic load rating C	415 kN
Basic static load rating C_0	455 kN
Fatigue load limit P_u	51 kN
Calculation factor k_r	0.23
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	7.13 kg
Angle ring	HJ 226 EC