



Bearing No. 51306

Size	30x60x21 mm
Bore Diameter	30 mm
Outer Diameter	60 mm
Width	21 mm
d	30 mm
D	60 mm
T	21 mm
d1	60 mm
r min.	1 mm
D1	32 mm
da min.	48 mm
Da max.	42 mm
ra max.	1 mm
Weight	0,269 Kg
Basic dynamic load rating (C)	43 kN
Basic static load rating (C0)	78,5 kN
(Grease) Lubrication Speed	2 800 r/min
Category	Thrust Ball Bearing
BDI Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.259
EAN	4547359307047
Product Group - BDI	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Single Direction

Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row With Flat Seat
Long Description	30MM Bore 1; 32MM Bore 2; 60MM Outside Diameter; 21MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; ABEC 1 ISO P0 Precision
Inch - Metric	Metric
Category - BDI	Thrust Ball Bearings
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	51306
Weight / LBS	0.59304
Outside Diameter	2.362 Inch 60 Millimeter
Bore 2	1.26 Inch 32 Millimeter
Height	0.827 Inch 21 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Bore 1	1.181 Inch 30 Millimeter
bore diameter:	30 mm
dynamic load capacity:	43000 N

outside diameter:	60 mm
operating temperature range:	-40 to 120 °C
overall width:	21 mm
maximum rpm:	3900 rpm
thrust bearing type:	Single-Direction
bearing material:	High Carbon Chrome Steel
outside diameter design:	Straight
cage material:	Resin
separable or banded:	Separable
fillet radius:	1 mm
precision rating:	ISO Class 0
series:	513
static load capacity:	78500 N
manufacturer product page:	Click here